



BASE CABINETS

MATERIALS - Stainless Steel, Type 300 Series, nickel-bearing.

GAUGES - Sides, bottom, rabbets, outer door pans, top railing, shelves - 18 gauge. Recessed base - 16 gauge. Drawers, back panels, inner door panels - 20 gauge.

CONSTRUCTION - Cabinets are constructed as complete and separate units, independent of adjacent units or additional components for rigidity or stability. Double walled drawers and doors close flush with the cabinet face to present a neat, clean appearance. Bottom of cabinet is fitted with a channel shaped base. Gussets with leveling bolts are welded into the corners accessible through button-covered holes punched in the cabinet bottoms. (Base is omitted when installation on masonry bases is specified). Attachment affects a toe space of approximately 3" x 4" high (7.62 x 10.16).

Doors are of double wall, telescoping pan construction, fitting into the rabbeted frame of the cabinet, and hung on semi-concealed, stainless steel hinges. Doors are equipped with die-cast aluminum bar pulls and spring activated nylon roller catches. Drawers are fabricated of one-piece, horizontally covered bodies mating with pan shaped, chamfered edged outer head, to form a double pan front, through which die cast aluminum bar pulls are secured. Drawers operate on ball bearing roller slides with full extension. Shelves are fabricated with channel shaped and flanged edges on all four sides and are adjustable on 1/2" (1.27) centers.

All base cabinets are 22" deep.

Single cabinets are also available in 21-1/8" width. Double-door cabinets are also available in 29" and 41" widths—consult factory. Countertops must be ordered separately—consult factory. Custom cabinets available on request.

BLICKMAN BASE CABINETS offer double walled solid doors for added strength and sound deadening for optimal performance.



Model No.	Part No.	Width	Height	Cupboard Shelves	Drawer Length	Drawer Height	Drawer Depth
AA18HS	2012118000	18-1/8" (46.04)	35-3/4" (90.81)	1	0		
AA24HS	2012224000	24-1/8" (61.28)	35-3/4" (90.81)	1	0		
AB18HS	2012218000	18-1/8" (46.04)	35-3/4" (90.81)	1	14-1/8" (35.88)	6-3/16" (15.72)	18-1/8" (46.04)
AB24HS	2012124000	24-1/8" (61.28)	35-3/4" (90.81)	1	20-1/8" (51.12)	6-3/16" (15.72)	18-1/8" (46.04)
AC18HS	2012218001	18-1/8" (46.04)	35-3/4" (90.81)	0	Fixed Panel with Louvres		
AC24HS	2012224001	24-1/8" (61.28)	35-3/4" (90.81)	0	Fixed Panel with Louvres		
AE18HS	2012318000	18-1/8" (46.04)	35-3/4" (90.81)	0	14-1/8" (35.88)	6-3/16" (15.72)	18-1/8" (46.04)
AE24HS	2012324000	24-1/8" (61.28)	35-3/4" (90.81)	0	20-1/8" (51.12)	6-3/16" (15.72)	18-1/8" (46.04)
AJ18HS	2012518000	18-1/8" (46.04)	35-3/4" (90.81)	2		Open	
AJ24HS	2012524000	24-1/8" (61.28)	35-3/4" (90.81)	2		Open	
AJ35HS	2012535000	35" (88.90)	35-3/4" (90.81)	2		Open	
AJ47HS	2012547000	47" (119.38)	35-3/4" (90.81)	2		Open	
AS18HS	2012718000	18-1/8" (46.04)	35-3/4" (90.81)	0	14-1/8" (35.88) 14-1/8" (35.88)	6-3/16" (15.72) 13-1/4" (33.66)	18-1/8" (46.04) 18-1/8" (46.04)
AS24HS	2012724000	24-1/8" (61.28)	35-3/4" (90.81)	0	20-1/8" (51.12) 20-1/8" (51.12)	6-3/16" (15.72) 13-1/4" (33.66)	18-1/8" (46.04) 18-1/8" (46.04)
DA35HS	2013235200	35" (88.90)	35-3/4" (90.81)	1	0		
DA47HS	2013247200	47" (119.38)	35-3/4" (90.81)	1	0		
DB35HS	2013235001	35" (88.90)	35-3/4" (90.81)	0	Fixed Panel with Louvres		
DB47HS	2013247000	47" (119.38)	35-3/4" (90.81)	0	Fixed Panel with Louvres		
DC35HS	2013235001	35" (88.90)	35-3/4" (90.81)	1	31" (78.74)	6-3/16" (15.72)	18-1/8" (46.04)
DC47HS	2013247001	47" (119.38)	35-3/4" (90.81)	1	43" (109.22)	6-3/16" (15.72)	18-1/8" (46.04)
DD35HS	2013335000	35" (88.90)	35-3/4" (90.81)	1	14-1/8" (35.88)	6-3/16" (15.72)	18-1/8" (46.04)
DD47HS	2013347000	47" (119.38)	35-3/4" (90.81)	1	20-1/8" (51.12)	6-3/16" (15.72)	18-1/8" (46.04)

NOTE: Metric dimensions are shown in centimeters. Specifications may be improved and dimensions changed without prior notice.