



**HIGH CABINETS**

**MATERIALS** - Stainless Steel, Type 300 Series, nickel-bearing, 1/4" (0.64) thick clear tempered glass.

**GAUGES** - Body, shelves, outer door pan or frame -18 gauge. Inner door pan or inserts - 20 gauge. Base -16 gauge. Leveling gussets -12 gauge.

**CONSTRUCTION** - Cabinets are constructed as floor and wall supported, individual cases with finished sides, designed to accommodate five adjustable shelves. Cabinets are provided with applied channel shaped bases, incorporating toe space recesses approximating 3" (7.62) deep and 4" (10.16) high. Gussets with leveling bolts are welded into the corners, accessible through button covered holes punched in the cabinet bottoms. Bases can be omitted when conditions dictate. Shelves are constructed with channel shaped and a flanged edge, adjustable on 1/2" (1.27) centers the full height of the cabinets. Solid doors are double wall, telescoping pans with interior channel reinforcing between pans. Glazed doors are double shell design, with a one-piece outer frame, die-formed to receive a rubber gasketed glass panel, held in place by removable insert strips. Doors are available either hinged or sliding, with hinged doors hung on three semi-concealed stainless steel hinges. Right hand hinged doors fitted with two point up and down knob latching, left hand doors with astragal, dummy knob and spring loaded nylon roller catch. Sliding doors are provided with semi-concealed, ball bearing sheaves set into the bottom edges of the doors, riding in stainless steel tracks top and bottom. Door frames are fitted with die-formed recessed pulls welded in place.


**WELDING** - All welding accomplished by heli-arc method. All exposed welds ground smooth.

**FINISH** - All exposed surfaces are free from pit marks, weld seams and scale, and polished to a satin finish.

**OPTIONS** - Sloping tops, additional shelves.

*Double-door cabinets are also available in 29" and 41" widths—consult factory.*

**BLICKMAN HIGH CABINETS** offer double walled solid doors for added strength and sound deadening for optimal performance. Sliding doors ride quietly on noiseless ball bearing rollers. Recessed base allows for convenient 3" x 4" toe space for easy access to cabinet. Bases can be eliminated when cabinet is recessed or other base is used.



Model No.	Part No.	Width	Height	Depth	Shelves
H18HAS	2030418000	18-3/4"(47.63)	84"(213.36)	18"(45.72)	5
H18HBS	2030418230	18-3/4"(47.63)	84"(213.36)	23"(58.42)	5
H24HAS	2030424000	24-3/4"(62.87)	84"(213.36)	18"(45.72)	5
H24HBS	2030424230	24-3/4"(62.87)	84"(213.36)	23"(58.42)	5
I35HAS	2030435000	35"(88.90)	84"(213.36)	18"(45.72)	5
I35HBS	2030435230	35"(88.90)	84"(213.36)	23"(58.42)	5
I47HAS	2030447000	47"(119.38)	84"(213.36)	18"(45.72)	5
I47HBS	2030447230	47"(119.38)	84"(213.36)	23"(58.42)	5
J35HAS	2030535180	35"(88.90)	84"(213.36)	18"(45.72)	5
J35HBS	2030535232	35"(88.90)	84"(213.36)	23"(58.42)	5
J47HAS	2030547180	47"(119.38)	84"(213.36)	18"(45.72)	5
J47HBS	2030547232	47"(119.38)	84"(213.36)	23"(58.42)	5
K18HAS	2030518000	18-3/4"(47.63)	84"(213.36)	18"(45.72)	5
K18HBS	2030518230	18-3/4"(47.63)	84"(213.36)	23"(58.42)	5
K24HAS	2030524000	24-3/4"(62.87)	84"(213.36)	18"(45.72)	5
K24HBS	2030524230	24-3/4"(62.87)	84"(213.36)	23"(58.42)	5
L35HAS	2030535000	35"(88.90)	84"(213.36)	18"(45.72)	5
L35HBS	2030535230	35"(88.90)	84"(213.36)	23"(58.42)	5
L47HAS	2030547000	47"(119.38)	84"(213.36)	18"(45.72)	5
L47HBS	2030547230	47"(119.38)	84"(213.36)	23"(58.42)	5
M35HAS	2030635000	35"(88.90)	84"(213.36)	18"(45.72)	5
M35HBS	2030635230	35"(88.90)	84"(213.36)	23"(58.42)	5
M47HAS	2030647000	47"(119.38)	84"(213.36)	18"(45.72)	5
M47HBS	2030647230	47"(119.38)	84"(213.36)	23"(58.42)	5

**Options:** *Sloping tops available for all models. Choice of solid or glass-hinged doors; sliding glass or solid doors; additional shelves.*

*Shelves are adjustable in 1/2" increments. It is recommended that these cabinets be securely anchored to adjacent surfaces. Custom Designs available on request.*

**NOTE:** *Metric dimensions are shown in centimeters.*

*Specifications may be improved and dimensions changed without prior notice.*



Sales and Service of Cardiology and Surgical Equipment and Supplies