THE BLICKMAN 8000 SERIES SURGICAL SCRUB SINKS offer all stainless steel construction with a clean design and low maintenance. OR staff can maintain standards of care for the surgical hand scrub by selecting water activation through an electronic infrared system with proximity sensor or knee-activated water. A swivel gooseneck spout with sterilizable spray rose aerator allows the user to control water flow while a deep sloping basin minimizes splash. Security features include automatic shutoff when temperature exceeds 115°F (46°C). An easy to remove panel provides access to plumbing and electrical components. A removable Plexiglas divider separates stations with multiple bays.

OPERATIONS:

Infrared Units: Water flow is activated through a continuous beam emitted from a sensor in the front of the sink. When the operator is in the range of the sink (approx. 18"), there is a 2 second delay before water flow is activated. It automatically shuts off after the operator moves out of the range of the sensor.

Knee-Activated Units: Water flow is activated through a one- touch on/off water valve. A removable, watertight, sloped control panel is located behind the faucet for accommodating mixing valve and soap spout. A thermostatically controlled mixing valve allows selection of water temperature up to 115°F.

INSTALLATION: Wall-mounted units are supported by a "Z" bracket and two main brackets supplied with the sink. It is recommended that a chair carrier be used for support. Connections required are 1/2" N.P.T. cold water, 1/2" N.P.T. hot water and 1-1/2" waste drain per station.

8882SS-IF

8882SS with optional knee-activated soap

Model No.	Mounting	Controls	Part No.	Width	Depth	Height	No. places
8881SS	wall mount	knee-activated	1388812000	32" (81.28)	27-1/2" (69.85)	37-1/8" (94.3)	1
8881SS-IF	wall mount	infrared sensor	1388812001	32" (81.28)	27-1/2" (69.85)	37-1/8" (94.3)	1
8881SS-FL	floor mount	knee-activated	1388811000	32" (81.28)	27-1/2" (69.85)	51-1/2" (130.81)	1
8881SS-FL-IF	floor mount	infrared sensor	1388811001	32" (81.28)	27-1/2" (69.85)	51-1/2" (130.81)	1
8882SS	wall mount	knee-activated	1388822000	64" (162.56)	27-1/2" (69.85)	37-1/8" (94.3)	2
8882SS-IF	wall mount	infrared sensor	1388822001	64" (162.56)	27-1/2" (69.85)	37-1/8" (94.3)	2
8882SS-FL	floor mount	knee-activated	1388821000	64" (162.56)	27-1/2" (69.85)	51-1/2" (130.81)	2
8882SS-FL-IF	floor mount	infrared sensor	1388821001	64" (162.56)	27-1/2" (69.85)	51-1/2" (130.81)	2
8883SS	wall mount	knee-activated	1388832000	96" (243.84)	27-1/2" (69.85)	37-1/8" (94.3)	3
8883SS-IF	wall mount	infrared sensor	1388832001	96" (243.84)	27-1/2" (69.85)	37-1/8" (94.3)	3
8883SS-FL	floor mount	knee-activated	1388831000	96" (243.84)	27-1/2" (69.85)	51-1/2" (130.81)	3
8883SS-FL-IF	floor mount	infrared sensor	1388831001	96" (243.84)	27-1/2" (69.85)	51-1/2" (130.81)	3

Options: Knee-activated soap, scrub timer with display, top storage shelf, pedestal base, in-wall chair carrier.

NOTE: *Metric dimensions are shown in centimeters.*

Specifications may be improved and dimensions changed without prior notice.

39 Robinson Road, Lodi, NJ 07644 • 800-247-5070 • Fax: 201-909-0832
e-mail: info@blickman.com • www.blickman.com

All shipping weights are estimates only and may be changed without prior notice. Specifications may be improved and dimensions changed without prior notice.
Unless otherwise noted, all products displayed or listed are deemed, MR-'Unsafe,' in accordance with ASTM Standard F2052-06.

Copyright © 2006 Blickman, Inc.