



MODELS 7925MG AND 7925MS warming cabinets are 24-1/2" high and primarily used for warming solutions. Quality and control features are the same as those on the larger models. An adjustable shelf comes standard. It is suggested that these units sit on an existing cabinet, or on a Blickman transport dolly or mobile stand. Easy-to-use keypad with controls for setting internal temperature is conveniently located above door. Solutions-only warming cabinets can be pre-programmed to heat between 90°F and 110°F.

Model No.	Part No.	Interior Cubic Foot Capacity	Dimensions (overall)	Shelves	AMPS	Total Wattage
7925MG	14D7925243	5.21	30"W 26-1/2"D 24-1/2"H	1	7.5	750
7925MS	14D7925200	5.21	30"W 26-1/2"D 24-1/2"H	1	7.5	750



MODELS 7927MG and 7927MS warming cabinets are a compact size for when space is at a premium. These single compartment counter-top warmers come standard with a glass door. An adjustable shelf and stainless steel door are available as an option. It measures 20-1/2" deep, allowing for placement on most counter or table-top surfaces. Unit is fully self-contained with no heat vents, as are all Blickman warmers. As a result, the unit is much more efficient and accuracy control is much easier. Solutions-only warming cabinets can be pre-programmed to heat between 90°F and 110°F.



Model No.	Part No.	Interior Cubic Foot Capacity	Dimensions (overall)	Shelves	AMPS	Total Wattage
7927MG	14D7927243	3.36	24"W 20-1/2"D 24-1/2"H	0	7.5	750
7927MS	14D7927200	3.36	24"W 20-1/2"D 24-1/2"H	0	7.5	750

MODELS SW30MG and SW30MS warming cabinets are used for warming solutions or blankets. Temperature control from 90°F–160°F. Digital temperature display, equipped with visual and audible alarms and an automatic safety switch to prevent overheating. Fan for even heat distribution. UL listed and CUL certified. Designed for recessed installation, the most common application for this unit would be a built-in OR wall console. Solutions-only warming cabinets can be pre-programmed to heat between 90°F and 110°F.

Model No.	Part No.	Interior Cubic Foot Capacity	Dimensions (overall)	Shelves	AMPS	Total Wattage
SW30MG	14D9930200	16.67	30"W 18"D 60"H	4	7.5	750
SW30MS	14D9930100	16.67	30"W 18"D 60"H	4	7.5	750



MODELS 7929MG 'READY WARMER' is new to the Blickman line. Used for warming solutions or blankets where space is at a premium and/or where multiple locations have modest warming requirements — buy one 'Ready Warmer' for each location! It is suggested that this unit sits on an existing cabinet, or on a Blickman transport dolly or mobile stand. Comes complete with digital control from 90°F to 140°F with keyed lockout, fan for even heat distribution, glass door, 120 volt, UL-listed and CUL-certified. Solutions-only warming cabinets can be pre-programmed to heat between 90°F and 110°F.

Model No.	Part No.	Interior Cubic Foot Capacity	Dimensions (overall)	Shelves	AMPS	Total Wattage
7929MG	14D7929243	1.145	18"W 15-9/16"D 22-1/8"H	0	5.8	700